

Endu[®]Combi RA

REGIONAL ALL POSITION

The Endu[®]Combi RA regional all position tire offers exceptional performance & casing durability.




ENHANCED STABILITY




Wide footprint and stone ejectors in all grooves help keep the tread clean & improve casing durability.

IMPROVED TRACTION




- Deep 3D sipes provide excellent traction throughout the tread life.
- Zig-Zag grooved walls help provide optimized biting edges for excellent traction in all seasonal conditions.

EVEN WEAR



Deep stress-relieving sipes assists in maintaining even wear and higher removal mileages.

MULTIPLE RETREADS



Robust construction with optimized belt package.

PRODUCT CODE	TIRESIZE	PLY RATING	LOAD RANGE	LOAD INDEX	SPEED SYMBOL	OVERALL DIA-METER (INCH)	SECTION WIDTH (INCH)	ORIGINAL TREAD DEPTH (1/32")	STATIC LOADED RADIUS (INCH)	RECOMMENDED RIM WIDTH (INCH)	ALTERNATE RIM WIDTH (INCH)	TIRES WEIGHT		LOAD DETAILS (LBS)	
												LBS	KG	SINGLE	DUAL
*2021104	225/70R19.5	14	G	128/126	L	32.2	8.9	16	14.9	6.75	6.00	71.0	32.2	3970 lbs @ 110 psi	3750 lbs @ 110 psi
2021110	295/75R22.5	14	G	144/141	L	40.2	11.5	20	18.7	9.00	8.25	127.4	57.8	6175 lbs @ 110 psi	5675 lbs @ 110 psi
2021109	295/75R22.5	16	H	149/146	L	40.2	11.5	20	18.7	9.00	8.25	127.4	57.8	7160 lbs @ 123 psi	6610 lbs @ 123 psi
2021106	11R22.5	14	G	144/142	L	41.2	11.1	20	19.3	8.25	7.50	129.0	58.5	6175 lbs @ 105 psi	5840 lbs @ 105 psi
2021105	11R22.5	16	H	146/143	L	41.2	11.1	20	19.3	8.25	7.50	129.0	58.5	6610 lbs @ 120 psi	6005 lbs @ 120 psi
2021107	255/70R22.5	16	H	140/137	M	36.6	9.9	17	17.1	7.50	6.75	129.0	42.9	5510 lbs @ 120 psi	5070 lbs @ 120 psi
*2021108	275/70R22.5	18	J	148/145	L	37.4	10.8	17	17.5	8.25	7.50	116.6	52.9	6940 lbs @ 130 psi	6395 lbs @ 130 psi
2021112	11R24.5	14	G	146/143	L	43.3	11.2	21	20.2	8.25	7.50	140.9	63.9	6610 lbs @ 105 psi	6005 lbs @ 105 psi
2021111	11R24.5	16	H	149/146	L	43.3	11.2	21	20.2	8.25	7.50	140.9	63.9	7160 lbs @ 120 psi	6610 lbs @ 120 psi

*Coming soon

