

Endu[®]Combi RA

REGIONAL ALL POSITION



The Endu[®]Combi RA regional all position tire offers exceptional performance & casing durability.

M + S


REGIONAL **SUPER REGIONAL**

SmartWay

6 YEARS WARRANTY*


ROAD HAZARD WARRANTY

ENHANCED STABILITY




Wide footprint and stone ejectors in all grooves help keep the tread clean & improve casing durability.

IMPROVED TRACTION




- Deep 3D sipes provide excellent traction throughout the tread life.
- Zig-Zag grooved walls help provide optimized biting edges for excellent traction in all seasonal conditions.

EVEN WEAR



Deep stress-relieving sipes assists in maintaining even wear and higher removal mileages.

MULTIPLE RETREADS



Robust construction with optimized belt package.

PRODUCT CODE	SIZE	LI/SS	PLY RATING/ LOAD RANGE	SEC-TION WIDTH (INCH)	OVERALL DIAMETER (INCH)	TIRE WEIGHT LBS	ORIGINAL TREAD DEPTH (1/32")	STATIC LOADED RADIUS (INCH)	RECOM-MENDED RIM WIDTH (INCH)	ALTERNATE RIM WIDTH (INCH)	ROLLING CIRCUM-FERENCE (INCH)	REVS/ MILE	LOAD DETAILS (LBS)	
													SINGLE	DUAL
2021110	295/75R22.5	144/141/L	14/G	11.5	40.2	127	20	18.7	9.00	8.25	121.8	512	6175 lbs @ 110 psi	5675 lbs @ 110 psi
2021109	295/75R22.5	149/146/L	16/H	11.5	40.2	127	20	18.7	9.00	8.25	121.8	512	7160 lbs @ 123 psi	6610 lbs @ 123 psi
2021106	11R22.5	144/142/L	14/G	11.1	41.2	129	20	19.3	8.25	7.50	126.1	499	6175 lbs @ 105 psi	5840 lbs @ 105 psi
2021105	11R22.5	146/143/L	16/H	11.1	41.2	129	20	19.3	8.25	8.25	126.1	499	6610 lbs @ 120 psi	6005 lbs @ 120 psi
2021107	255/70R22.5	140/137/M	16/H	9.9	36.6	129	17	17.1	7.50	6.75	111.7	560	5510 lbs @ 120 psi	5070 lbs @ 120 psi
*2021108	275/70R22.5	148/145/L	18J	10.8	37.4	117	17	17.5	8.25	7.50	114.9	TBC	6940 lbs @ 130 psi	6395 lbs @ 130 psi
2021111	11R24.5	146/143/L	14/G	11.2	43.3	141	21	20.2	8.25	7.50	132.6	475	6610 lbs @ 105 psi	6005 lbs @ 105 psi
2021112	11R24.5	149/146/L	16/H	11.2	43.3	141	21	20.2	8.25	7.50	132.6	475	7160 lbs @ 120 psi	6610 lbs @ 120 psi