

LOAD INFLATION CHART



Guidelines according to rim size and axle position
Standard reference : T&RA & ETRTO

TIRE DESCRIPTION & MARKINGS				TIRE LOAD LIMITS (KG. / .LBS) AT VARIOUS COLD INFLATION PRESSURES. PRESSURE LISTED IS THE MINIMUM FOR THE LOAD																	
Usage segment	Tire Size	Tire Name	Axle Position	Single/Dual Fitment	Bar	4,80	5,20	5,50	5,90	6,20	6,60	6,90	7,20	7,60	7,90	8,30	8,50	8,75	9,00		
					Kpa	480	520	550	590	620	660	690	720	760	790	830	850	875	900		
					Psi	70	75	80	85	90	95	100	105	110	115	120	123	125	130		
Longhaul 22.5	295/75R22.5	EnduMile LHfront	Front	S	kg. .lbs	2040 4500	2140 4725	2240 4940	2340 5155	2440 5370	2500(F) 5510(F)	2620 5780	2710 5980	2800(G) 6175(G)	2890 6370			*3250 (H) 7160(H)			
				D	kg. .lbs	1860 4095	1950 4300	2060 4540	2130 4690	2220 4885	2300(F) 5070(F)	2390 5260	2470 5440	2575(G) 5675(G)	2630 5795			*3000 (H) *6610(H)			
	295/75R22.5	EnduMile LHD	Drive	S	kg. .lbs	2040 4500	2140 4725	2240 4940	2340 5155	2440 5370	2500(F) 5510(F)	2620 5780	2710 5980	2800(G) 6175(G)	2890 6370			*3250 (H) 7160(H)			
				D	kg. .lbs	1860 4095	1950 4300	2060 4540	2130 4690	2220 4885	2300(F) 5070(F)	2390 5260	2470 5440	2575(G) 5675(G)	2630 5795			*3000 (H) *6610(H)			
	295/75R22.5	EnduMile LHT	Trailer	S	kg. .lbs	2040 4500	2140 4725	2240 4940	2340 5155	2440 5370	2500(F) 5510(F)	2620 5780	2710 5980	2800(G) 6175(G)	2890 6370			*3250 (H) 7160(H)			
				D	kg. .lbs	1860 4095	1950 4300	2060 4540	2130 4690	2220 4885	2300(F) 5070(F)	2390 5260	2470 5440	2575(G) 5675(G)	2630 5795			*3000 (H) *6610(H)			
Regional 17.5	215/75R17.5	EnduCombi RT	Trailer	S	kg. .lbs		1350 2980	1420 3135	1495 3295	1565 3445	1635 3660	1700(G) 3750(G)									
				D	kg. .lbs		1270 2800	1340 2950	1405 3095	1470 3240	1535 3385	1600(G) 3525(G)									
	235/75R17.5	EnduCombi RT	Trailer	S	kg. .lbs							2300 5070	2350 5180	2400 5290	2450 5400	2600 5730	2650 5840	2725(J) 6005(J)			
				D	kg. .lbs								2150 4740	2225 4905	2275 5015	2325 5125	2450 5400	2525 5565	2575(J) 5675(J)		
	245/70R17.5	EnduCombi RT	Trailer	S	kg. .lbs							2300 5070	2350 5180	2400 5290	2450 5400	2600 5730	2650 5840	2725(J) 6005(J)			
				D	kg. .lbs								2150 4740	2225 4905	2275 5015	2325 5125	2450 5400	2525 5565	2575(J) 5675(J)		
Regional 22.5	255/70R22.5	EnduCombi RA	All Position	S	kg. .lbs	1730 3815	1820 4005	1900 4190	1980 4370	2060 4550	2120 4675	2220 4895	2300 5065	2360(G) 5205(G)	2450 5400	2500(H) 5510(H)					
				D	kg. .lbs	1630 3585	1710 3765	1800 3970	1860 4110	1940 4275	2000 4410	2020 4455	2090 4610	2120(G) 4675(G)	2230 4915	2300(H) 5070(H)					
	295/75R22.5	EnduCombi RA	All Position	S	kg. .lbs	2040 4500	2140 4725	2240 4940	2340 5155	2440 5370	2500 5510	2620 5780	2710 5980	2800(G) 6175(G)	2890 6370			*3250 (H) 7160(H)			
				D	kg. .lbs	1860 4095	1950 4300	2060 4540	2130 4690	2220 4885	2300 5070	2390 5260	2470 5440	2575(G) 5675(G)	2630 5795			*3000 (H) *6610(H)			
	295/75R22.5	EnduCombi RD CS EnduCombi RD OS	Drive	S	kg. .lbs	2040 4500	2140 4725	2240 4940	2340 5155	2440 5370	2500 5510	2620 5780	2710 5980	2800(G) 6175(G)	2890 6370			*3250 (H) 7160(H)			
				D	kg. .lbs	1860 4095	1950 4300	2060 4540	2130 4690	2220 4885	2300 5070	2390 5260	2470 5440	2575(G) 5675(G)	2630 5795			*3000 (H) *6610(H)			
	295/75R22.5	EnduCombi RT	Trailer	S	kg. .lbs	2040 4500	2140 4725	2240 4940	2340 5155	2440 5370	2500 5510	2620 5780	2710 5980	2800(G) 6175(G)	2890 6370			*3250 (H) 7160(H)			
				D	kg. .lbs	1860 4095	1950 4300	2060 4540	2130 4690	2220 4885	2300 5070	2390 5260	2470 5440	2575(G) 5675(G)	2630 5795			*3000 (H) *6610(H)			
	11R22.5	EnduCombi RA	All Position	S	kg. .lbs	2050 4530	2160 4770	2260 4990	2370 5220	2500 5510	2600 5730	2700 5950	2800(G) 6175(G)	2870 6320	2940 6465	3000(H) 6610(H)					
				D	kg. .lbs	1990 4380	2080 4580	2160 4760	2250 4950	2360 5205	2460 5415	2560 5625	2650(G) 5840(G)	2680 5895	2710 5950	2725(H) 6005(H)					
	11R22.5	EnduCombi RD CS EnduCombi RD OS	Drive	S	kg. .lbs	2050 4530	2160 4770	2260 4990	2370 5220	2500 5510	2600 5730	2700 5950	2800(G) 6175(G)	2870 6320	2940 6465	3000(H) 6610(H)					
				D	kg. .lbs	1990 4380	2080 4580	2160 4760	2250 4950	2360 5205	2460 5415	2560 5625	2650(G) 5840(G)	2680 5895	2710 5950	2725(H) 6005(H)					
11R22.5	EnduCombi RT	Trailer	S	kg. .lbs	2050 4530	2160 4770	2260 4990	2370 5220	2500 5510	2600 5730	2700 5950	2800(G) 6175(G)	2870 6320	2940 6465	3000(H) 6610(H)						
			D	kg. .lbs	1990 4380	2080 4580	2160 4760	2250 4950	2360 5205	2460 5415	2560 5625	2650(G) 5840(G)	2680 5895	2710 5950	2725(H) 6005(H)						
Regional 24.5"	11R24.5	EnduCombi RA	All Position	S	kg. .lbs	2190 4820	2300 5070	2410 5310	2520 5550	2650 5840	2770 6095	2890 6350	3000(G) 6610(G)	3080 6790	3160 6970	*3250(H) 7160(H)					
				D	kg. .lbs	2110 4660	2210 4870	2300 5070	2390 5260	2500 5510	2580 5675	2660 5840	2725(G) 6005(G)	2820 6205	2910 6405	*3000(H) 6610(H)					
	11R24.5	EnduCombi RD CS EnduCombi RD OS	Drive	S	kg. .lbs	2190 4820	2300 5070	2410 5310	2520 5550	2650 5840	2770 6095	2890 6350	3000(G) 6610(G)	3080 6790	3160 6970	*3250(H) 7160(H)					
				D	kg. .lbs	2110 4660	2210 4870	2300 5070	2390 5260	2500 5510	2580 5675	2660 5840	2725(G) 6005(G)	2820 6205	2910 6405	*3000(H) 6610(H)					
Mixed 22.5"	11R22.5	EnduTrax MA	All Position	S	kg. .lbs	2050 4530	2160 4770	2260 4990	2370 5220	2500 5510	2600 5730	2700 5950	2800 6175	2870 6320	2940 6465	3000 6610	*3150(H) *6940(H)				
				D	kg. .lbs	1990 4380	2080 4580	2160 4760	2250 4950	2360 5205	2460 5415	2560 5625	2650 5840	2680 5895	2710 5950	2725 6005	*2900(H) *6395(H)				
	11R22.5	EnduTrax MD	Drive	S	kg. .lbs	2050 4530	2160 4770	2260 4990	2370 5220	2500 5510	2600 5730	2700 5950	2800 6175	2870 6320	2940 6465	3000 6610	*3150(H) *6940(H)				
				D	kg. .lbs	1990 4380	2080 4580	2160 4760	2250 4950	2360 5205	2460 5415	2560 5625	2650 5840	2680 5895	2710 5950	2725 6005	*2900(H) *6395(H)				
	11R22.5	EnduTuff SOD	Drive	S	kg. .lbs	2050 4530	2160 4770	2260 4990	2370 5220	2500 5510	2600 5730	2700 5950	2800 6175	2870 6320	2940 6465	3000 6610	*3150(H) *6940(H)				
				D	kg. .lbs	1990 4380	2080 4580	2160 4760	2250 4950	2360 5205	2460 5415	2560 5625	2650 5840	2680 5895	2710 5950	2725 6005	*2900(H) *6395(H)				
	12R22.5	EnduTrax MA	All Position	S	kg. .lbs	2240 4940	2360 5200	2470 5445	2580 5690	2725 6000	2820 6215	2910 6415	3000 6615	3120 6880	3240 7145	3350 7385	*3550(H) *7830(H)				
				D	kg. .lbs	2170 4785	2260 4980	2350 5180	2440 5380	2575 5675	2630 5780	2680 5900	2725 6010	2840 6260	2960 6525	3075 6780	*3150(H) *6940(H)				
	12R22.5	EnduTrax MD	Drive	S	kg. .lbs	2240 4940	2360 5200	2470 5445	2580 5690	2725 6000	2820 6215	2910 6415	3000 6615	3120 6880	3240 7145	3350 7385	*3550(H) *7830(H)				
				D	kg. .lbs	2170 4785	2260 4980	2350 5180	2440 5380	2575 5675	2630 5780	2680 5900	2725 6010	2840 6260	2960 6525	3075 6780	*3150(H) *6940(H)				
	315/80R22.5	EnduTrax MA	All Position	S	kg. .lbs		2660 5875	2800 6175	2910 6415	3030 6670	3150(G) 6940(G)	3260 7190	3370 7440	3450(H) 7610(H)	3590 7920	3750(J) 8270(J)	3940 8690	4125(L) / **4625 (L) 9090(L) / **10200(L)			
				D	kg. .lbs		2420 5345	2575 5675	2650 5840	2750 6070	2900(G) 6395(G)	2970 6545	3070 6770	3150(H) 6940(H)	3270 7210	3450(J) 7610(J)	3590 7910	3750(L) / **4125 (L) 8270(L) / **9090(L)			
315/80R22.5	EnduTrax MD	Drive	S	kg. .lbs		2660 5875	2800 6175	2910 6415	3030 6670	3150(G) 6940(G)	3260 7190	3370 7440	3450(H) 7610(H)	3590 7920	3750(J) 8270(J)	3940 8690	4125(L) / **4625 (L) 9090(L)				
			D	kg. .lbs		2420 5345	2575 5675	2650 5840	2750 6070	2900(G) 6395(G)	2970 6545	3070 6770	3150(H) 6940(H)	3270 7210	3450(J) 7610(J)	3590 7910	3750(L) / **4125 (L) 8270(L) / **9090(L)				
385/65R22.5	EnduTrax MAHD	All Position	S	kg. .lbs	2880 6380	3060 6720	3150 6940	3350 7350	3470 7650	3650 8050	3740 8230	3850 8510	4000 8820	4100 9050	4250 (J) 9370(J)	4340 9570	4500 (L) / *5000 (M) 9920(M) / *11000(M)				
Mixed 24.5	11R24.5	EnduTrax MA	All Position	S	kg. .lbs	2190 4820	2300 5070	2410 5310	2520 5550	2650 5840	2770 6095	2890 6350	3000 6610	3080 6790	3160 6970	*3250(H) 7160(H)					
				D	kg. .lbs	2110 4660	2														