

Endu[®]Combi RT

REGIONAL TRAILER

The Endu[®]Combi RT is a multi life, free rolling trailer tire with high scrub resistance.




Copyright © 2024, Apollo Tires

HIGH SCRUB RESISTANCE




Solid rounded shoulder rib optimized for high scrub trailer applications.

EVEN WEAR



Deep stress-relieving sipes helps in maintaining even wear and higher removal mileages.

LONGER TREAD LIFE



Long tread life from tough, cool-running tread compound, offering maximum resistance to excessive scrub.

MULTIPLE RETREADS



Combination of superior tread design with robust belt package for enhanced durability.

PRODUCT CODE	TIRE SIZE	PLY RATING	LOAD RANGE	LOAD INDEX	SPEED SYMBOL	OVERALL DIA-METER (INCH)	SECTION WIDTH (INCH)	ORIGINAL TREAD DEPTH (1/32")	STATIC LOADED RADIUS (INCH)	RECOM-MENDED RIM WIDTH (INCH)	ALTERNATE RIM WIDTH (INCH)	TIRE WEIGHT		LOAD DETAILS (LBS)	
												LBS	KG	SINGLE	DUAL
2021600	215/75R17.5	16	H	135/133	K	30.3	8.4	17	14.2	6.00	6.75	68.6	31.1	4805 lbs @123 psi	4540 lbs @123 psi
2021601	235/75R17.5	16	H	143/141	K	31.5	9.4	17	14.6	6.75	7.50	76.5	34.7	6005 lbs @125 psi	5675 lbs @ 125 psi
2021602	245/70R17.5	16	H	143/141	K	31.1	9.8	17	14.5	7.50	6.75	75.4	34.2	6005 lbs @125 psi	5675 lbs @ 125 psi
2021610	295/75R22.5	14	G	144/141	L	40.0	11.4	16	18.7	9.00	8.25	115.5	52.4	6175 lbs @ 110 psi	5675 lbs @ 110 psi
2021609	295/75R22.5	16	H	149/146	L	40.0	11.4	16	18.7	9.00	8.25	115.5	52.4	7160 lbs @ 123 psi	6610 lbs @123 psi
2021605	11R22.5	14	G	144/142	L	40.9	11.1	16	19.3	8.25	7.50	120.6	54.7	6175 lbs @ 105 psi	5840 lbs @ 105 psi
2021604	11R22.5	16	H	146/143	L	40.9	11.1	16	19.3	8.25	7.50	120.6	54.7	6610 lbs @120 psi	6005 lbs @120 psi

APOLLO TIRES (US) INC. 6 Concourse Parkway Building 6, Suite 2920, Atlanta, GA 30328
+1 (877) 234 0867 contact.us@apollotyres.com

